

### EP3 coated replacement spring (right side)

Due to product improvements, springs of different size and finish are specified for replacement in certain doors. To verify that this is the correct replacement for your application, consider the shipment date if known, and compare the original specification on the table below to the spring that you will be replacing.

Left/Right side is as observed when standing inside the storage unit looking out at the door. In standard Trac-Rite applications, the latch side is the left side.

#### For 944 shipped in or after January 2012:

Width range: 11'1" to 12'0"

Height range: 10'5" to 12'0"

#### For 955 shipped 1998 to present:

Width range: 8'0" to 9'11"

Height range: 0'0" to 4'5", 7'10" to 11'11"

#### For 988 door (used as center spring on certain sizes):

Width range: 13'7" to 16'0"

Height range: 11'2" to 16'0"

Refer to Trac-Rite Spring Replacement Guide Table for greater application detail.



	Original Spring	Replacement Spring
Wire Diameter	.283"	.283"
Inside Diameter	3.375"	3.375"
Nominal Length	19.5"	19.5"
No. of Coils	83	83
Inch Number Per Turn (IPPT)	62	62

Corresponding left side spring is 600971

THIS DRAWING AND ALL PARTS THEREOF ARE THE EXCLUSIVE PROPERTY OF TRAC-RITE DOOR, INC. AND MAY NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT WRITTEN PERMISSION.



314 Wilburn Road, Sun Prairie, WI 53590  
Phone: 800-448-8979 Fax: 800-236-8722  
www.tracrite.com

DATE 11/30/11

DESCRIPTION  
SPRING, DOOR, RIGHT

BY SJH APP'D JL

DRAWING NO.  
600961

REV.  
--

SHEET  
1 OF 1