





INDUSTRIAL • COMMERCIAL • AGRICULTURAL

MODEL 988WL

Less than 2:12 Roof Pitch

Less ula				
Door Width	PSF	Exposure Cat B (MPH)	Exposure Cat C (MPH)	Exposure Cat D (MPH)
10'0"	32	197	164	149
11'0"	32	198	164	150
12'0"	29	189	157	143
13'0"	24	175	145	133
14'0"	24	175	145	133
15'0"	21	164	136	124
16'0"	21	164	136	124

Greater than 2:12 Roof Pitch

Door Width	PSF	Exposure Cat B (MPH)	Exposure Cat C (MPH)	Exposure Cat D (MPH)
10'0"	32	189	157	143
11'0"	32	190	157	144
12'0"	29	181	150	137
13'0"	24	168	139	127
14'0"	24	168	139	127
15'0"	21	157	130	119
16'0"	21	157	130	119





- * Based upon 16 ft. Door Height
- * Based upon 4 ft. or greater from the building corner

ASCE7-16

B: Urban and suburban areas, wooded areas, or other terrain with numerous closely spaced obstructions having the size of single-family dwellings or larger.

Based upon mean roof height of 20 ft.

All pressures are negative ratings

Based upon a 40'x120' building footprint

- C: Open terrain with scattered obstructions having heights generally less than 30 feet.
- D: Flat, unobstructed areas exposed to wind flowing over large bodies of water.

