

Jamb Brush Seal

Description: Weather strip fabricated from black polypropylene filament brush in a mill finish aluminum extrusion. Attaches to side jamb.

Application: Designed to eliminate air infiltration. Recommended for use in wide-open space, dusty weather conditions, and with the insulation accessory.



Exterior Latch

Description: Cast zinc alloy with black nickel finish. Latch slide has magnetic properties for use with security system switches. Designed to accommodate two padlocks up to 7/16" shank. Accommodates Trac-Rite's optional SpaceGuard cylinder lock which features an easy over-lock system. The lock does not penetrate the door.

Application: Provides secure exterior locking capabilities to a single entrance.



SpaceGuard Cylinder Lock

Description: Removable security cylinder features easy over-lock capability and protection from bolt cutters. Each cylinder lock comes with three coded keys.

Application: Provides added security, especially for unfenced areas.



Header Draft Stop (Field Installed)

Description: 4" wide, consists of a 1" rigid PVC strip and 3" flexible TPE section. Attaches to the header.

Application: Designed to seal the top of the door to eliminate air infiltration. Recommended for use in wide-open space, dusty weather conditions, and with the insulation accessory.



Passport™ Locking Solution

Description: The Passport Lock is a keyless locking system using WAN (Wide Area Network) to lock and unlock doors. A DirectKey Mobile App enables the user to lock and unlock the door using their mobile phone.

Application: The Passport Locking Solution offers a convenient locking system that is ideal for self-storage facilities. The system can unlock entry & exit gates, doors, and units with a tap on a smartphone. No more forgotten keys & cutting locks.



Insulation (Factory Installed)

Description: Double bubble foil reflective insulation with an extra layer of polyurethane coating on the front side for durability.


Application: Helps maintain desired temperature in heated building applications. Header draft stop and jamb brush seals are recommended with insulated doors.



Interior Lock

Description: 12-gauge, zinc-coated steel slide bolt engages a lock strike attached to the side guide. Two locks per door fasten to the bottom assembly and are suitable for padlocking.

Application: Recommended where interior access is needed, for example, counter shutter applications.



Hood

Description: Covers the door nest and chain hoist. (Will not cover motor operator.) Available in Iced White only.

Application: Keeps the door nest clean, protects the mechanisms from weather, and aesthetically pleasing.



For more information

PHONE 800 448 8979
 FAX 800 236 8722
 WEBSITE www.tracrite.com
 EMAIL tr@tracrite.com
 ADDRESS 314 Wilburn Road
 Sun Prairie, WI 53590