

988

ROLL UP DOORS



**988 & 988WL
ROLL UP DOORS**

INDUSTRIAL • COMMERCIAL • AGRICULTURAL

MODEL 988/988WL

Less than 2:12 Roof Pitch

Door Width	PSF	Exposure Cat B (MPH)	Exposure Cat C (MPH)	Exposure Cat D (MPH)
10'0"	-52.8/+48.0	262	215	196
11'0"	-48.0/+43.6	251	206	187
12'0"	-44.0/+40.0	241	198	180
13'0"	-40.2/+36.6	231	190	172
14'0"	-37.3/+34.0	223	183	166
15'0"	-34.1/+29.9	216	177	161
16'0"	-32.0/+28.0	209	172	156
17'0"	-30.1/+26.4	203	166	151
18'0"	-28.4/+24.9	197	162	147

Greater than 2:12 Roof Pitch

Door Width	PSF	Exposure Cat B (MPH)	Exposure Cat C (MPH)	Exposure Cat D (MPH)
10'0"	-52.8/+48.0	251	206	187
11'0"	-48.0/+43.6	240	197	179
12'0"	-44.0/+40.0	231	189	172
13'0"	-40.2/+36.6	221	181	165
14'0"	-37.3/+34.0	213	175	159
15'0"	-34.1/+29.9	207	170	154
16'0"	-32.0/+28.0	200	164	149
17'0"	-30.1/+26.4	194	159	145
18'0"	-28.4/+24.9	189	155	141



TDI# GDR-159
FL# 8055.1



CODE APPROVED

- * Based upon 16 ft. Door Height
- * Based upon 4 ft. or greater from the building corner

ASCE7-16

- B: Urban and suburban areas, wooded areas, or other terrain with numerous closely spaced obstructions having the size of single-family dwellings or larger.
- C: Open terrain with scattered obstructions having heights generally less than 30 feet.
- D: Flat, unobstructed areas exposed to wind flowing over large bodies of water.

- * Based upon mean roof height of 20 ft.
- * Based upon a 40'x120' building footprint
- * All pressures are negative ratings

Contact your Trac-Rite sales representative for rating based upon your specific project:

800.448.8979 | Fax 800.236.8722

tracrite.com | tr@tracrite.com

314 Wilburn Rd, Sun Prairie, WI 53590

ATBS COMPANY