

### Jamb Brush Seal

**Description:** Weather strip fabricated from black polypropylene filament brush in a mill finish aluminum extrusion. Attaches to side jamb.


**Application:** Designed to eliminate air infiltration. Recommended for use in wide-open space, dusty weather conditions, and with the insulation accessory.



### Insulation (Factory Installed)

**Description:** Double bubble foil reflective insulation with an extra layer of polyurethane coating on the front side for durability.

**Application:** Helps maintain desired temperature in heated building applications. Header draft stop and jamb brush seals are recommended with insulated doors.



### Exterior Latch

**Description:** Cast zinc alloy with powder coated grey finish. Latch slide has magnetic properties for use with security system switches. Designed to accommodate two padlocks up to 7/16" shank. Accommodates Trac-Rite's optional SpaceGuard cylinder lock which features an easy over-lock system. The lock does not penetrate the door.

**Application:** Provides secure exterior locking capabilities to a single entrance.



### Interior Lock

**Description:** 12-gauge, zinc coated steel slide bolt engages a lock strike attached to the side guide. Two locks per door fasten to the bottom assembly and are suitable for padlocking.

**Application:** Recommended where interior access is needed, for example, counter shutter applications.



### SpaceGuard Cylinder Lock

**Description:** Removable security cylinder features easy over-lock capability and protection from bolt cutters. Each cylinder lock comes with three coded keys.

**Application:** Provides added security, especially for unfenced areas.



### Hood

**Description:** Covers the door nest and chain hoist. (Will not cover motor operator.) Available in Iced White only.

**Application:** Keeps the door nest clean, protects the mechanisms from weather, and aesthetically pleasing.



### Header Draft Stop (Field Installed)

**Description:** 4" wide, consists of a 1" rigid PVC strip and 3" flexible TPE section. Attaches to the header.

**Application:** Designed to seal the top of the door to eliminate air infiltration. Recommended for use in wide-open space, dusty weather conditions, and with the insulation accessory.



### For more information

800.448.8979  
800.236.8722 (Fax)  
tr@tracrite.com  
tracrite.com

314 Wilburn Rd  
Sun Prairie, WI 53590

**A TBS COMPANY**